



Without RS232

47" High-Definition LCD Panel Display

ST-HB47A1X

Specifications

Digital Signage

LCD PANEL

Brightness 620cd / m² (Typical)

Contrast Ratio 800 : 1

Viewing Angle H:176 ° / V:176 °

Response Time 8 ms (GTG)

Supported colors 16.7M colors

Resolution 1920 x 1080

DISPLAY FEATURES

Horizontal Frequency 30K ~ 90KHz

Vertical Frequency 50 ~ 85Hz

Input Resolution 1920 x 1080 @ 60 Hz (Analog)
1920 x 1080 @ 60 Hz (Digital)

DDC DDC 2B

OSD Control Push button, IR Remote Controller

OSD Language English

Video Signal Type RGB Analog / Digital

Connector 15 pin D-Sub / DVI /
Component / S-video / AV

PHYSICAL FEATURES

Power Supply AC 100 or 220V

Dimension W/O Stand 1139.4 x 124.4 x 684.4 mm (W×H×D)

Diagonal 47"

Weight W/O Stand Net: 38.7kg Gross: 45.7kg

Wall / Arm Mount Type 200mm × 200mm , 200mm × 800mm VESA

Multimedia PIP, PAP, Zoom

AV / TV W/O TV Tuner

Audio N / A

SPECIAL FEATURES

Fanless design No

Stand Optional

Normal Operation less then 290W

Suspend / Standby less then 20W

POWER CONSUMPTION

Power off Mode less then 20W

COMPLIANCE

CE, FCC, VCCI, BSMI, CCC,
CB, UL/CUL, TUV/PS, ROHS / WEEE

OPTIONS

Power saving mode
Open SKD format

All specifications subject to change without notice.